

The new Benchmark: The X-SLIM from PFERD
Cutting with the thinnest



NEW



- The extremely thin straight wheel with unrivaled performance
- Ultimate speed and aggressiveness
- Unique cutting convenience

The new benchmark: The X-SLIM from PFERD

Special Line SG-PLUS

INOX
Hard type - hardness grade S



Extremely sleek high-power tool in S-INOX hardness.

New PFERD version with ultimate cutting performance and unrivaled tool life:

- extremely cool,
- very fast,
- especially convenient,
- supremely low-burr.

Abrasive: Aluminium oxide A

Manufactured without addition of ferrous, sulphurous and chlorinated fillers.

Workpiece materials:

Stainless steel (INOX)



Application:

Cutting thin-walled sheets and profiles


Recommendation for use:

The X-SLIM produces a convincing cutting performance even on low-output drive machines.

The X-SLIM from PFERD meets all the safety requirements of EN 12413.

Order No.	EAN 4007220	Grit size	EN- designation	D x T x H [mm (Inch)]	Max. speed [RPM]		
Depressed centre type (form 42)							
EH 115-0,8 A 60 S SGP-INOX X-SLIM	669327	60	42 A 60 S BF 80	115 x 0,8 x 22,23 (7/8)	13.300	25	0,500
EH 125-0,8 A 60 S SGP-INOX X-SLIM	669334	60	42 A 60 S BF 80	125 x 0,8 x 22,23 (7/8)	12.200	25	0,625
Flat type EHT (form 41)							
N! EHT 115-0,8 A 60 S SGP-INOX X-SLIM	835357	60	41 A 60 S BF 80	115 x 0,8 x 22,23 (7/8)	13.300	25	0,500
N! EHT 125-0,8 A 60 S SGP-INOX X-SLIM	835364	60	41 A 60 S BF 80	125 x 0,8 x 22,23 (7/8)	12.200	25	0,625


PFERDERGONOMICS recommends cut-off wheel X-SLIM as an innovative tool solution. For further information and suitable PFERD tools see the brochure "PFERDERGONOMICS – The focus is on people".



Vibration Filter



Noise Filter



Emission Filter



Haptic Filter

